

European Headquarters

Tiger-Vac Europa S.R.L.
Via Marie Curie 17
Zona Industriale Ponte Rizzoli
Ozzano Emilia, BO 40064

Tel: ((39) 051 79.53.52)
Fax: ((39) 051 4695077)
Website: <http://www.tiger-vac.eu>
Email: info@tiger-vac.it

International Headquarters

Tiger-Vac International Inc.
2020 Dagenais Blvd. Ouest
Laval, Quebec
Canada H7L 5W2

Tel: (450-625-0099)
Fax: (450-625-3388)
Website: <http://www.tiger-vac.com>
Email: sales@tiger-vac.com



Certification Externe ATEX
CE 0081 II 1/3 D
Ex tc IIIC T200°C Dc IP6X
c T3
LCIE 15 ATEX 3061

Zone 20 (Poussières) niveau de protection
très élevé à l'intérieur de la cuve de
récupération
*Pour la Récupération des Poussières
Combustibles*



Antistatique



HEPA - inclus



Haute efficacité
de filtration



Acier
Inoxydable



Accessoires
antistatiques -
inclus



Récupération
des poussières



Certifié EX

Certification IECEx 3ème partie



Ex tc IIIC T200°C Dc IP6X
IECEx LCIE 15.0048

Ce modèle peut être utilisé pour récupérer
les Poussières Combustibles tel que les
Groupes de Poussières :



IIIA Poussières Combustibles (fibres de
coton, copeaux de bois, etc.)
IIIB Poussières non-Combustibles
(poussière de farine, poussière de grain,
sucre, amidon, bois, plastique, carbone,
charbon, etc.)
IIIC Poussières Conductrices (poussière
métallique combustible, aluminum,
magnesium, alliages commerciaux)

Aspirateurs antistatiques pour Zones à
risque d'explosion, conçus pour prévenir les
risques d'inflammation.
Nous utilisons des pièces métalliques ou
peintes avec un revêtement antistatique afin
d'éviter les décharges électrostatiques (ESD)

Certifié **ATEX** 1ère partie avec moteur
"brushless"
CE 0081 II 3 D
Ex tc IIIC T200°C Dc IP6X

Spécifications for C-10 EX (4W)

Name	Part Number	Tension	Fréquence	Phase	Puissance électrique	Puissance	Ampérage	Flux d'air	Pression sous vide	Type de la prise d'alimentation	Récupération des poussières - sac filtrant jetable
C-10 EX (4W)	111805B	220-240 V	50/60 Hz	Unique	1200 W	1.2 kW	5 A	194 m³/h	2504 mm H ₂ O	Non inclus	19 L
Dimensions: H93 cm x W43 cm x L43 cm Weight: 24 kg. Sound Level: 72 dB(A)											
Description: Equipped with a Universal Motor. Manufacturer motor performance only on an orifice of Ø2" (Ø50mm). Results may vary.											

C-10 EX (4W) SS304 TANK	111805B-304	220-240 V	50/60 Hz	Unique	1200 W	1.2 kW	5 A	194 m³/h	2504 mm H₂O	Non inclus	19 L
	Dimensions: H93 cm x W43 cm x L43 cm Weight: 24 kg. Sound Level: 72 dB(A)										
Description: With stainless steel SAE 304 recovery tank											

C-10 EX (4W) BLSD	111805B-BLSD	220-240 V	50/60 Hz	Unique	1100 W	1.3 kW	8 A	215 m³/h	2250 mm H₂O	Européen	19 L
	Dimensions: H93 cm x W43 cm x L43 cm Weight: 24 kg. Sound Level: 72 dB(A)										
Description: With Brushless Motor											

Veuillez noter que les spécifications peuvent être modifiées sans préavis

Feuille technique for C-10 EX (4W)

HEPA FILTERS - Included	
Numero de la pièce	Description
212304B-HD	HEPA FILTER, 99.99% EFFICIENCY ON 0.3 MICRON, HEAVY DUTY CONSTRUCTION
215372	HEPA FILTER WITH GASKETS ON BOTH SIDES, 99.99% ON 0.3 MICRON, 11.522" OD x 9.066" ID x 2" HIGH
211854	HEPA FILTER (H14) WITH GASKET, 2"(50mm) HIGH

FILTERS AND ACCESSORIES - Included	
Numero de la pièce	Description
219046A	MAIN FILTER ASSEMBLY SD* FOR C-10 EX VACS WITH 4 LACES FOR WHITE FILTER CAGE (CAGE SOLD SEPARATELY)

HIGH TEMPERATURE MAIN FILTER - Optional	
Numero de la pièce	Description
212359	HIGH TEMPERATURE MAIN FILTER ASMBLY w/GASKET w/RING w/LACES SD* FOR C-10 EX(4W)-CAGE SOLD SEPARATELY

CONDUCTIVE RECOVERY BAG - Included	
Numero de la pièce	Description
212994-SD	COLLECTION BAGS MADE OF CONDUCTIVE MATERIAL (PKG OF 3)

POLY LINER RECOVERY BAGS AND ACCESSORIES - Included	
Numero de la pièce	Description
212100S	CONDUCTIVE POLY LINER WITH DRAW STRING (40 LITRES/10 GALLONS)

POLY LINER RECOVERY BAGS AND ACCESSORIES - Optional	
Numero de la pièce	Description
212100S-5	CONDUCTIVE POLY LINER WITH DRAW STRING (40 LITRES/10 GALLONS)(PACKAGE OF 5)

TOOLS AND ACCESSORIES - Included	
Numero de la pièce	Description
383440D	STATIC CONDUCTIVE CRUSHPROOF SUCTION HOSE ASMBLY 1.5"(38mm) x 10'(3m)FOR USE w/60mm CONDUCTIVE INLET
381208	CURVED HANDLE, 1.5" TO 1.25" (38mm TO 32mm), CHROME, WITH BUTTON LOCK & AIRFLOW REGULAR
323315	EXTENSION WANDS, 1.25" (32mm) SET OF 2, CHROME WITH HOLE FOR BUTTON LOCK
323318A	UTILITY FLOOR TOOL, Ø1.25"(Ø32mm) x 12"(30cm), STATIC CONDUCTIVE PLASTIC w/CONDUCTIVE NYLON BRISTLES
323312A	ROUND BRUSH, 1.25"(32mm) x 3"(7.5cm), ESD SAFE PLASTIC, WITH HOLE FOR BUTTON LOCK
323313A	CREVICE TOOL, 1.25"(32mm) x 8"(20cm), BLACK, ESD SAFE PLASTIC w/HOLE FOR BUTTON LOCK
323314A	UPHOLSTERY FLAT TOOL, 1.25"(32mm) x 5"(13cm), ESD SAFE PLASTIC

TOOLS AND ACCESSORIES - Optional	
Numero de la pièce	Description
381477	DOUBLE BEND WAND (2pc) 1.5" (38mm) x 54" (137cm), CHROME, w/TAPER FOR PLASTIC FLOOR TOOLS
381448A	UTILITY FLOOR TOOL, Ø1.5"(Ø38mm) x 12"(30cm), STATIC CONDUCTIVE PLASTIC w/CONDUCTIVE NYLON BRISTLES
383312A	ROUND BRUSH ASSEMBLY, ESD SAFE PLASTIC, FOR USE WITH 1.5" (38mm) HOSE
381818	CREVICE TOOL 1.5"(38mm) x 8"(20cm) w/1.5" ALUMINUM TUBE, BLACK RUBBER, CONDUCTIVE & OIL RESISTANT



2, rue André Citroën 95130 FRANCONVILLE - Site : www.sterigene.com
Tél. : +33 (0)1 34 44 23 23 - Fax : +33 (0)1 34 44 23 24 - e-mail : sterigene@sterigene.com